Internal Thread Lift Bottom Check Valve



PRODUCT OVERVIEW

Body material:	Gray cast iron		
Size range:	DN15 ~ 50mm		
Pressure rating:	0.25MPa		
Operating temperature:	0 ~ 50°C		
End connection:	Threaded		
Applicable medium:	Water		
Mode of operation:	Manual		
Applicable industry:	Water & Water treatment, Power generation, Pulp & Paper, Municipal, Heating & Ventilation		
Design & Manufacture:	API, ASME, ASTM, ANSI, BS, DIN, JIS, ISO, GB		

DESIGN FEATURES

- 1. It features reasonable compact structure with small volume, and the valve body has a streamlined and beautiful appearance.
- 2. The opening and closing torque is small, and the sealing is safe and reliable.
- 3. Without any external force, it can be opened and closed by pipeline pressure and dead weight.
- 4. It features shape simple, good manufacturing process, and wide scope of application.

VALVE MATERIAL LIST

Part Name	Part Material	
Valve body, Bonnet	Grey cast iron	
Valve clack	Grey cast iron	
Gasket	Natural rubber	
Valve seat	Grey cast iron	
Bolts and Nuts	35/25	

TECHNICAL SPECIFICATIONS

Model	DN	G	D	L
H12X-2.5	32	1 1/4	98	98
	40	1 1/2	116	110
	50	2	144	130



